





CONNECTOR A		CABLE CHARACTERISTICS				CONNECTOR B	
IMPEDANCE	50 OHM	IMPEDANCE	50 OHMS	SHIELDS	2 SHIELD TINNED COPPER / ALUMINUM TAPE	IMPEDANCE	50 OHM
BODY	BRASS TRI-METAL PLATED	JACKET	.195" Ø POLYETHYLENE	NOMINAL CAPACITANCE	24.5 PF/FOOT	BODY	BRASS TRI-METAL PLATED
CONTACT	SILVER PLATED	DIELECTRIC	.116" Ø FPE	MAX OPERATING VOLTAGE	3,000 VOLTS RMS	CONTACT	SILVER PLATED
INSULATOR	PTFE	CENTER CONDUCTOR	.044 Ø BARE COPPER	OPERATING TEMPERATURE	-40°C TO +85°C	INSULATOR	PTFE





Bracke Manufacturing, LLC
 PO Box 12319
 Newport Beach, Ca 92658
 Phone (949)756-1600 / Fax (949) 756-1601
 sales@brackemfg.com / www.brackemfg.com

Part Number		Description	CAGE / NAGE	
BM92650.**		7/16 DIN Male Right Angle Low PIM to 7/16 DIN Male Right Angle Low PIM, Cable Assembly using LMR®-200 Cable	6LOW2	
Produced By	Checked By	Notes • Bracke Manufacturing, LLC reserves the right to change any specifications at any time in its sole discretion without notice. • The depiction above was produced by and is the sole property of Bracke Manufacturing, LLC and may not be copied or reproduced in any manner without Bracke's prior written consent. • Standard cable length tolerance is ± 1.5% or 3/8 inch, whichever is greater • Replace ** with ANY length in Inches	Scale	Unit
002	013		1:1	Inches
			Date	Revision
		©2025 Bracke Manufacturing, LLC	06/24/2025	A-01



BRACKE
 Bracke Manufacturing, LLC

LMR® is a registered trademark of Times Microwave Systems