

MATERIALS

BODY	BRASS TRI-METAL PLATED
CONTACTS	GOLD PLATED
INSULATOR	PTFE

PERFORMANCE

IMPEDANCE (OHM)	50
FREQUENCY RANGE (GHz)	.1 - 3
VSWR (MAX)	1.35:1
INPUT POWER (WATTS)	2
DC CURRENT (mA MAX)	100
VOLTAGE RATING (VOLTS MAX)	100
ATTENUATION (dB)	20
ACCURACY (dB TYP.)	+/- 5
OPERATING TEMP. RANGE (°C)	-50 to +80

Technical drawing of the BM10058.20 attenuator. The drawing shows a side view of the device with dimensions: a diameter of .630 Ø, a length of 2.312, and a thread specification of .4375-28 UNEF-2A. The word 'BRACKE' is printed on the side of the device.

3D perspective view of the BM10058.20 attenuator, showing its cylindrical shape and threaded end.

Scale 1:1

Bracke Manufacturing, LLC
PO Box 12319
Newport Beach, Ca 92658
Phone (949)756-1600 / Fax (949) 756-1601
sales@brackemfg.com / www.brackemfg.com

Part Number		Description	CAGE / NAGE	
BM10058.20			6LOW2	
Produced By	Checked By		Scale	Unit
002	017		Date	Revision
		Notes		
		<ul style="list-style-type: none">Bracke Manufacturing, LLC reserves the right to change any specifications at any time in its sole discretion without notice.The depiction above was produced by and is the sole property of Bracke Manufacturing, LLC and may not be copied or reproduced in any manner without Bracke's prior written consent.		
		©2024 Bracke Manufacturing, LLC		