

MATERIALS

BODY	PASSIVATED STAINLESS STEEL
CONTACTS	GOLD PLATED
INSULATOR	PTFE

OPERATIONAL SPECIFICATIONS

IMPEDANCE (OHM)	50
FREQUENCY RANGE (GHz)	.05 - 3
VSWR (MAX)	1.35:1
INPUT POWER (WATTS)	2
DC CURRENT (AMPS MAX)	2
VOLTAGE RATING (VOLTS MAX)	100
ATTENUATION (dB)	10
ACCURACY (dB TYP.)	+/- 2.00
OPERATING TEMP. RANGE (°C)	-55 to +85

5/8" HEX

BRACKE

2.065

.4375 - 28 UNEF - 2A

Scale 1:1

RoHS COMPLIANT

BRACKE

Bracke Manufacturing, LLC

<div>Bracke Manufacturing, LLC PO Box 12319 Newport Beach, Ca 92658 Phone (949) 756-1600 / Fax (949) 756-1601 sales@brackemfg.com / www.brackemfg.com</div>	Part Number		Description		CAGE / NAGE	
	BM10058.10		TNC Male to Female, 10 dB		6LOW2	
			50 Ohm [DC Bias Passing Attenuator, Max VSWR 1.35:1 @ 3 GHz]		Scale	Unit
	Produced By		Checked By		Date	Revision
	002		014		11/14/2024	A-01

- Bracke Manufacturing, LLC reserves the right to change any specifications at any time in its sole discretion without notice.
- The depiction above was produced by and is the sole property of Bracke Manufacturing, LLC and may not be copied or reproduced in any manner without Bracke's prior written consent.

©2024 Bracke Manufacturing, LLC