

M
A
T
E
R
I
A
L
S

BODY	PASSIVATED STAINLESS STEEL
CONTACTS	GOLD PLATED
INSULATOR	PTFE

E
P
L
E
O
C
P
T
E
R
I
T
C
I
A
E
L
S

IMPEDANCE (OHM)	50
FREQUENCY RANGE (GHz)	.05 - 3
VSWR (MAX)	1.35:1
INPUT POWER (WATTS)	2
DC CURRENT (AMPS MAX)	2
VOLTAGE RATING (VOLTS MAX)	100
ATTENUATION (dB)	10
ACCURACY (dB)	+/- 2.00
OPERATING TEMP. RANGE (°C)	-55 to +85

.800 Ø

BRACKE

1.758

.625 - 24 UNEF - 2A

Scale 1:1

BRACKE
Bracke Manufacturing, LLC

Bracke Manufacturing, LLC PO Box 12319 Newport Beach, Ca 92658 Phone (949)756-1600 / Fax (949) 756-1601 sales@brackemfg.com / www.brackemfg.com	Part Number		Description		CAGE / NAGE	
	BM10056.10		N Male to Female, 10 dB 50 Ohm [DC Bias Passing Attenuator, Max VSWR 1.35:1 @ 3 GHz]		6LOW2	
	Produced By	Checked By	Notes		Scale	Unit
	002	014	- Bracke Manufacturing, LLC reserves the right to change any specifications at any time in its sole discretion without notice. - The depiction above was produced by and is the sole property of Bracke Manufacturing, LLC and may not be copied or reproduced in any manner without Bracke's prior written consent. ©2024 Bracke Manufacturing, LLC		2:1	Inches
					Date	Revision
				1/05/2024	A-01	