




CHARACTERISTICS


IMPEDANCE	50 OHMS
INSULATION RESISTANCE	5,000 ΜΩ
OPERATING FREQUENCY	5 GHz
DIELECTRIC WITHSTANDING VOLTAGE	6,000 Vrms
VSWR TYPICAL	1.35:1
INSERTION LOSS TYPICAL	.06 √ Freq. GHz
OPERATING TEMPERATURE	-65 to +165 C°
VOLTAGE RATING	2,100 VOLTS
INTERFACE	IEC 50-22-2
VIBRATION	MIL-STD-202 METHOD 204, CONDITION A
CORROSION	MIL-STD-202 METHOD 101, CONDITION B
















Scale 1/2:1

Bracke Manufacturing, LLC

ROHS

PO Box 12319

Newport Beach, Ca 92658

Phone (949)756-1600 / Fax (949) 756-1601 sales@brackemfg.com / www.brackemfg.com

Part Number		
BM6	1556	
Produced By	Checked By	

014

002

7/8" EIA Right Angle

50 Ohm, Clamp Connector [7/8" Cable BM-LDF5, LDF5-50, AVA5-50, AL5-50, LCF78-50, EC5-50]

Description

Bracke Manufacturing, LLC reserves the right to change any specifications at any time in its sole discretion without notice. The depiction above was produced by and is the sole property of Bracke Manufacturing, LLC and may not be copied or reproduced in any manner without Bracke's prior written consent. ©2024 Bracke Manufacturing, LLC

	CAGE / NAGE 6L0W2		
a	Scale	Unit	
J	1/2:1	Inches	
	Date	Revision	
	6/27/2024	A-01	