



O - RING **ELECTRICAL & ENVIRONMENTAL CHARACTERISTICS**

IMPEDANCE	50 OHM	
INSULATION RESISTANCE	5000 ΜΩ	
OPERATING FREQUENCY	22 GHz	
DIELECTRIC WITHSTANDING VOLTAGE	1000 Vrms	
VSWR TYPICAL	1.25:1	
INSERTION LOSS TYPICAL	.06 √ Freq. GHz	
OPERATING TEMPERATURE	-65 to +165 C°	
VOLTAGE RATING	500 VOLTS	
INTERFACE	MIL-STD-348	
VIBRATION	MIL-STD-202 METHOD 204, CONDITION A	
CORROSION	MIL-STD-202 METHOD 101, CONDITION B	





Bracke Manufacturing, LLC



BRACKE

Bracke Manufacturing, LLC PO Box 12319

RoHS

Newport Beach, Ca 92658

Phone (949)756-1600 / Fax (949) 756-1601 sales@brackemfg.com / www.brackemfg.com

Part Number	
BM6	1779
Produced By	Checked By

014

002

Description	
BMA Plug .500" Panel Mount, Flush Dielect	ric
050 X .005 Captive Tab Contact [Connector]	

reproduced in any manner without Bracke's prior written consent.

BMA Plug .500" Panel Mount, Flush Dielectric		6L0	
050 X .005 Captive Tab Contact [Connector]		ĺ	
		ı	
Notes	Date	ĺ	
Bracke Manufacturing, LLC reserves the right to change any specifications at any time in its sole discretion without notice. The depiction above was produced by and is the sole property of Bracke Manufacturing, LLC and may not be copied or	4/01/2025	ĺ	

	CAGE / NAGE		
Dielectric	6L0W2		
	Scale	Unit	
nector]	3:1	Inches	
	Date	Revision	
ons at any time in its sole discretion without notice. Manufacturing, LLC and may not be copied or ©2025 Bracke Manufacturing, LLC	4/01/2025	A-01	