

MATERIALS	SMA CONNECTORS	BRASS NICKEL PLATED
	CONTACTS	GOLD PLATED
	INSULATOR	PTFE
ELECTRICALS	FREQUENCY RANGE (GHz)	7 - 12.4
	VSWR (MAX)	1.30:1
	INSERTION LOSS (dB MAX)	0.50
	ISOLATION (dB MIN)	18
	AVERAGE POWER (WATTS)	25
	PEAK POWER (WATTS)	500
	OPERATING TEMP (°C)	-30 to +85

.380

.250 - 36 UNS - 2A

.340

.080

BRACKE

1

2

3


#0 - 80 UNF - 2B  
x .10 DP x 2

.375

.500

.570

.390



**Bracke Manufacturing, LLC**  
PO Box 12319  
Newport Beach, Ca 92658  
Phone (949) 756-1600 / Fax (949) 756-1601  
sales@brackemfg.com / www.brackemfg.com

Part Number	
<b>BM13307</b>	
Produced By	Checked By
002	013

Description	
<b>SMA Female, 10 Watts, Max VSWR 1.30:1 @ 12.4 GHz</b> 50 Ohm [Circulator]	
Notes	
<ul style="list-style-type: none"><li>Bracke Manufacturing, LLC reserves the right to change any specifications at any time in its sole discretion without notice.</li><li>The depiction above was produced by and is the sole property of Bracke Manufacturing, LLC and may not be copied or reproduced in any manner without Bracke's prior written consent.</li></ul> <div>©2020 Bracke Manufacturing, LLC</div>	

CAGE / NAGE	
6LOW2	
Scale	Units
1:1	Inches
Date	Revision
10/06/2015	A-01