

M A T E R - A L Ø	BODY	PASSIVATED STAINLESS STEEL
	CONTACTS	GOLD PLATED
	INSULATOR	PTFE
	IMPEDANCE (OHM)	50
	FREQUENCY RANGE (GHz)	.05 - 3
EP	VSWR (MAX)	1.35:1
LR EO CP	INPUT POWER (WATTS)	2
TE RR	DC CURRENT (AMPS MAX)	2
IT CI AE LS	VOLTAGE RATING (VOLTS MAX)	100
	ATTENUATION (dB)	3
	ACCURACY (dB TYP.)	+/- 2.00
	OPERATING TEMP. RANGE (°C)	-55 to +85





BRACKE Bracke Manufacturing, LLC

Scale 1:1

BRACKE

Bracke Manufacturing, LLC PO Box 12319

RoHS

Newport Beach, Ca 92658

Phone (949)756-1600 / Fax (949) 756-1601 sales@brackemfg.com / www.brackemfg.com

Part Number	
BM10	058.3
Produced By	Checked By

002

007

TNC Male to Female, 3 dB

50 Ohm [DC Bias Passing Attenuator, Max VSWR 1.35:1 @ 3 GHz]

Notae	

Bracke Manufacturing, LLC reserves the right to change any specification	ns at any time in its sole discretion without notice.
The depiction above was produced by and is the sole property of Bracke	Manufacturing, LLC and may not be copied or
reproduced in any manner without Bracke's prior written consent.	©2024 Bracke Manufacturing LLC

CAGE / NAGE		
6L0W2		
Scale	Unit	
2:1	Inches	
Date	Revision	
11/14/2024	A-01	