






MATERIALS	
BODY	BRASS NICKEL PLATED
OUTER BODY	PBT
CONTACT	GOLD PLATED
INSULATOR	PTFE

HARDWARE	
	
NUT	WASHER

ELECTRICAL & ENVIRONMENTAL CHARACTERISTICS	
IMPEDANCE	75 OHMS
INSULATION RESISTANCE	5000 MΩ
OPERATING FREQUENCY	4 GHz
DIELECTRIC WITHSTANDING VOLTAGE	1000 Vrms
VSWR TYPICAL	1.30:1
INSERTION LOSS TYPICAL	.06 √ Freq. GHz
OPERATING TEMPERATURE	-65 to +165 C°
VOLTAGE RATING	500 VOLTS
INTERFACE	MIL-STD-348
VIBRATION	MIL-STD-202 METHOD 204, CONDITION A
CORROSION	MIL-STD-202 METHOD 101, CONDITION B



 <b>Bracke Manufacturing, LLC</b> PO Box 12319 Newport Beach, Ca 92658 Phone (949)756-1600 / Fax (949) 756-1601 sales@brackemfg.com / www.brackemfg.com	Part Number		Description	CAGE / NAGE	
	<b>BM51056</b>			6LOW2	
	Produced By	Checked By	<b>Notes</b>  • Bracke Manufacturing, LLC reserves the right to change any specifications at any time in its sole discretion without notice. • The depiction above was produced by and is the sole property of Bracke Manufacturing, LLC and may not be copied or reproduced in any manner without Bracke's prior written consent. <div>©2023 Bracke Manufacturing, LLC</div>	Scale	Unit
	002	007		2.5:1	Inches
				Date	Revision
				6/23/2023	A-01