

MATERIALS

BNC CONNECTORS	BRASS NICKEL PLATED
CONTACTS	GOLD PLATED
INSULATORS	PTFE

OPERATIONAL SPECIFICATIONS

IMPEDANCE (OHM)	75
FREQUENCY RANGE (MHz)	DC - 500
VSWR (MAX)	1.30:1
INPUT POWER (WATTS)	1
PEAK POWER (WATTS)	1000
ATTENUATION RANGE (dB)	0 - 45.5 dB in .5 dB STEPS
ATTENUATION STEPS (dB)	.5, 1, 2, 4, 8, 10 and 20
ACCURACY (dB)	+/- .5
INSERTION LOSS (dB MAX)	1.20
OPERATING TEMP. RANGE (°C)	-20 to +85

BRACKE MANUFACTURING

#4 - 40 X .25 DP X 4

RECOMMENDED MOUNTING HOLES

Bracke Manufacturing, LLC
PO Box 12319
Newport Beach, Ca 92658
Phone (949)756-1600 / Fax (949) 756-1601
sales@brackemfg.com / www.brackemfg.com

Part Number		Description	CAGE / NAGE	
BM10045			6LOW2	
Produced By	Checked By		Scale	Unit
002	014	3/4:1 Inches		
		Notes	Date	Revision
		- Bracke Manufacturing, LLC reserves the right to change any specifications at any time in its sole discretion without notice. - The depiction above was produced by and is the sole property of Bracke Manufacturing, LLC and may not be copied or reproduced in any manner without Bracke's prior written consent.	1/05/2024	A-01

©2024 Bracke Manufacturing, LLC